Koehler BrightStar Cap Lamps

Earning The Confidence & Trust Of Miners For Over 100 Years

These underground lighting solutions are the latest results of our 100+ years commitment to mining safety.

FEATURES:

- **Regulated, Consistent Light Output- optimum brightness maintained for entire run time**
- **Optimized Central & Peripheral Vision**
- **High/Low Lighting Modes**
- **LED Charge Status Indicator**
- **Automatic Low Power Detection & Indication (LI-6000-G model)**
- **Tracking & Proximity Available on the LI-5300-G model.**

Cordless LED Cap Lamp
Model# LI-6000-G


Includes Swivel Accessory and Rechargeable li-ion battery

SPECIFICATIONS:

- 65 Lumens
- 6,000 Candela
- 140 Meters Beam Distance
- Impact Resistance: 1 Meter
- Ingress Protection: IP68
- 15 hrs. run time high / 60 hrs. low
- Powered by Single Lithium Ion 18650 (2600 mAh Capacity)
- Light Source: LED
- 6 hr. Charge Time
- WEIGHT: 5 oz. with batteries
- SIZE: 3.4″ x 2.4″ x 2.7″
- Operating Temperature: -20°C to +60°C

SAFETY RATINGS:

- MSHA Part 19 Certified
- ATEX Ex ia | Ma Certified
- IECEx Ex ia | Ma Certified



LED Cap Lamp
Model# LI-5300-G

Includes cord and Rechargeable li-ion battery

SPECIFICATIONS:

- 91 Lumens
- 7,000 Candela
- 158 Meters Beam Distance
- 28 hrs. run time high / 250 hrs. low
- Impact Resistance: 1 Meter
- Ingress Protection: IP68
- Powered by 14.4 Ah Lithium Ion Battery
- Light Source: LED
- <8 hr. Charge Time
- WEIGHT: 1.9 lbs. with batteries
- SIZE: Lamp 2.1″W x 2.7″D
- Battery 3.5″W x 2.5″D x 5.2″H
- Cord 53″L
- Operating Temperature: -20°C to +60°C

SAFETY RATINGS:

- MSHA Part 18 Certified
- MSHA Part 19 Certified



To purchase Koehler BrightStar Cap Lamp products in the USA, please contact

UNITED CENTRAL INDUSTRIAL SUPPLY®

423-573-7300
Fax-Purchasing: 423-573-7399
www.unitedcentral.net